

GROENINK'S  
MATERIAL AND DATA SHEET  
GET A GRIP

Date Prepared: 2/13/16

**I. Product Identity**

PRODUCT NAME: 13-26-12 50% XCU

MFR INFO: Groenink's Elevator and Hardware  
11260 Michigan Ave.  
Nunica, MI 49448

FOR EMERGENCY: (800) 424-9300 (CHEMTREC)  
FOR INFORMATION: (616) 837-7391

CURRENT AS OF: 3/26/16

**II. Ingredient List**

Potash  
Monoammonium Phosphate  
Duration-45  
Urea  
Dolomite Lime

**III. Ingredient: Potash**

Product Name	:	<b>Potash</b>
Product Form	:	Mixture
Product Code	:	GRA, SOG, STD, SUS
Other Identification	:	Muriate of Potash: Granular, Standard, and Suspension Grades, WST
Use of substance	:	Fertilizer
Physical state	:	solid
Appearance	:	Granular solid. Fine to 4 mm size.
Color	:	White to red
Odour	:	Slightly oily
Odour threshold	:	No data available
pH	:	7 (approximately)
Melting point	:	771 – 773 °C (1420 – 1423 °F)
Freezing point	:	No data available
Boiling point	:	1420 – 1500 °C (2588 – 2732 °F)

Flash point	:	Not available
Self ignition temperature	:	Not flammable
Decomposition temperature	:	No data available
Flammability	:	Not flammable
Vapour pressure	:	80 Pa at 20°C
Density	:	1.98 g/cc
Solubility	:	Water: 347 g/l (at 20°C)
Explosive limits	:	Not explosive
Explosive properties	:	None known
Oxidizing properties	:	None known
VOC content	:	< 0.5 %
Reactivity	:	Stable at ambient temperature and under normal conditions of use.
Chemical stability	:	Stable at standard temperature and pressure.
Possibility of hazards	:	Hazardous polymerization will not occur.
Conditions to avoid	:	Protect from moisture.
Incompatible materials	:	Contact with acids liberates toxic gas (chlorine). Contact with hot nitric acid may produce toxic nitrosyl chloride.
Hazardous decomposition	:	Contact with strong acids may produce hydrogen chloride gas.

#### Products

#### **Firefighting Measures**

Suitable extinguishing media:	:	Not flammable. Use extinguishing media appropriate for surrounding fire.
Fire hazard	:	Under conditions of fire this material may produce: Potassium oxides; Hydrogen chloride; Chlorine gas.
Explosion hazard	:	Product is not explosive.
Reactivity	:	Stable at ambient temperature and under normal conditions of use.
Firefighting instructions	:	Keep upwind. Under conditions of fire this material may produce: Potassium oxides; Hydrogen chloride; Chlorine gas.
Protection during fire fighting:	:	Wear full fire-fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA).

Other Information : Do not allow run off from fire fighting to enter drains or water courses.

**GHS-US classification**

Eye Irrit. 2B H320

**GHS-US labelling**

Signal word (GHS-US) : Warning

Hazard statements (GHS-US): H320 – Causes eye irritation

Precautionary statements : P264 – Wash hands thoroughly after handling  
P305+P351+P338 – If in eyes:Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P337+P313 – If eye irritation persists: Get medical advice/attention.

**Toxicological Information**

Acute toxicity : Not classified

<b>Potash</b>	
Additional information	Potassium chloride is listed by the FDA as “Generally Recognizes as Safe” (GRAS and may be used as a food additive according to prescribed conditions.
<b>Potassium Chloride (7447-40-7)</b>	
LD50 oral rat	2600 mg/kg
<b>Sodium Chloride (7647-14-5)</b>	
LD50 oral rat	3 g/kg
LD50 dermal rabbit	> 10 g/kg
LC50 inhalation rat (mg/l)	> g/m <sup>3</sup> (Exposure time: 1 hr)

**Ecological Information**

Ecotoxicity:	
Acute toxicity to fish:	(Lepomis macrochirus) (blue gill) – 96 hour –

	LC <sub>50</sub> = 2010 mg/L (ppm KCl)
Chronic toxicity to fish:	No data available
Acute toxicity to aquatic invertebrates:	(Daphnia magna) – 48 hours – EC <sub>50</sub> – 337 – 825 mg/L; (Physa heterostropha) – 96 hrs – LC <sub>50</sub> = 940 mg/L.
Chronic Toxicity to Aquatic Invertebrates:	No data available
Toxicity to aquatic plants:	((Nitzshia linearis)diatom) – 5 days – 120 hour TIm = 1,337 ppm KCl; (Scendesmus subspicatus) 72 hour - EC <sub>50</sub>
Toxicity to bacteria: (activated)	No data available
Toxicity to soil dwelling organisms:	No data available
Toxicity to terrestrial plants:	No data available

**Enviromental Fate:**

Stability in Water:	Ions can persist, dissociates in water
Stability in Soil:	Binds to clay particles
Transport and Distribution:	1.51 x 10 <sup>-8</sup> % to air; 45.2% to water; 54.7% to soil; 0.0755% to sediment

**Toxicity:**

Not toxic to aquatic organisms defined by USEPA

**Degration Products:**

Biodegradation:	No data available
Photodegradation:	No data available

**US State Regulations**

Potash	SARA Sectin 311/312	Immediate (acute) health hazard
Potassium Chloride (7447-40-7)	Listed on the United States TSCA (Toxic	

	Substances Control Act) inventory
Sodium Chloride (7647-14-5)	Listed on the United States TSCA (Toxic Substances Control Act) inventory

Full text of H- phrases:

Eye Irrit. 2	Serious eye damage/eye irritation (Category 2)
Skin Irrit. 2	Skin corrosion/irritation (Category 2)
STOT SE 3	Specific target organ toxicity (single exposure) (Category 3)
H315	Causes skin irritation
H319	Causes serious eye irritation
H335	May cause respiratory irritation

#### **IV. Ingredient: Monoammonium Phosphate**

Product Form	:	Substance
Substance Name	:	<b>Monoammonium Phosphate (MAP)</b>
Uses of Substance	:	Agricultural chemical
GHS-US Classification:		
Skin Irrit. 2 H315		
Eye Irrit. 2B H320		
STOT SE 3 H335		
Signal Word	:	Warning
Engineering Control	:	Ensure adequate ventilation, especially in confined areas to avoid high dust concentration.
Personal Protection	:	Gloves, safety glasses, and protective clothing.
Hand Protection	:	Impermeable protective gloves.
Eye Protection	:	Protective goggles.
Physical State	:	Solid
Appearance	:	Granular solid
Molecular Mass	:	115g/mol

Color : Black to green

Odour : Odourless

pH : 4.2

pH Solution : 0.2 M at 25°C (aqueous solution)

Melting Point : 190°C (374°F)

Freezing Point : No data available

Boiling Point : Decomposes

Flash Point : No data available

Self Ignition Temperature : Not flammable

Flammability : Not flammable

Vapour Pressure : < 1mm Hg (at 20°C)

Relative Density : No data available

Density : 60-64 lbs/ft<sup>3</sup> (loose); 65-72 lbs/ft<sup>3</sup> (tamped)

Solubility : Soluble; Water: 328 g/l (at 20°C)

Viscosity : No data available

Name	Product Identifier	%	GHS-US classification
Monoammonium phosphate as P <sub>2</sub> O <sub>5</sub>	(CAS No.) 7722-76-1	52	Skin Irrit. 2 H315 Eye Irrit. 2B H320 STOT SE 3 H335
Total Nitrogen, as N***		11	
Fluorides, as F		0.6	

\*\*\* Product contains monoammonium phosphate as essential ingredient with small amounts of diammonium phosphate, ammonium sulfate, urea, and aluminum/calcium/iron/magnesium phosphate compounds.

Monoammonium Phosphate (7722-26-1) as P <sub>2</sub> O <sub>5</sub>		
USA ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> – inhalable fraction 3 mg/m <sup>3</sup> – respirable fraction
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	15 mg/m <sup>3</sup> – particulate 3 mg/m <sup>3</sup> - respirable
Fluorides		
USA ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	2.5 mg/m <sup>3</sup>
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	2.5 mg/m <sup>3</sup>

Hazard Statements : H315 – Causes skin irritation  
H320 – Causes eye irritation

H335 – May cause respiratory irritation  
H401 – Toxic to aquatic life

Precautionary statements : P261 – Avoid breathing dust  
P264 – Wash hands thoroughly after handling  
P271 – Use only outdoors or in a well-ventilated area  
P273 – Avoid release to the environment  
P280 – Wear eye protection, face protection, protective clothing, protective gloves  
P302+P352 – If on skin, wash with plenty of water  
P304+P340 – If inhaled, remove person to fresh air and keep comfortable for breathing  
P305+P351+P338 – If in eyes, rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.  
P312 – Call a Poison Center/ doctor if you feel unwell  
P332+P313 – If skin irritation occurs, get medical attention/advice  
P337+P313 – If eye irritation persists, get medical attention/advice  
P362 – Take off contaminated clothing  
P403+P233 – Store in a well-ventilated place. Keep container tightly closed.  
P405 – Store locked up  
P501 – Dispose of contents/container according to local, regional, national, and international regulations.

### **Stability and Reactivity**

Reactivity – Stable at ambient temperature and under normal conditions of use.

Chemical stability – Stable at standard temperature and pressure.

Possibility of hazardous reactions – Hazardous polymerization will not occur.

Conditions to avoid – Welding or hot work on equipment or plant which may have contained fertilizer should not be done without first washing thoroughly to remove all fertilization.

Incompatible materials – Alkalis and caustic products; strong acids; copper and its alloys.

Hazardous decomposition products – Ammonia is released upon reaction with strong bases or from thermal decomposition.

## Waste Treatment Methods

Sewage disposal recommendations – This material is hazardous to the aquatic environment. Keep out of sewers and waterways.

Waste disposal recommendations – place in an appropriate container and dispose of the contaminated material at a licensed site.

Addition information – Dispose of waste material in accordance with all local, regional, national, and international regulations.

## Toxicological Information

Monoammonium Phosphate	
LD50 oral rat	> 2000 mg/kg OECD Guideline 425
LD50 dermal rat	>5000 mg/kg OECD Guideline 402
Additional information	This compound is listed by the FDA as generally recognized as safe (GRAS) and may be used as a food additive, for both human food and ruminant feed, according to the prescribed conditions.
Monoammonium phosphate (7722-76-1)	
LD50 oral rat	5750 mg/kg
LD50 dermal rabbit	> 7940 mg/kg

Skin corrosion/irritation : Causes skin irritation. pH: 4.2 (0.2 M solution)

Serious eye damage/irritation: Causes eye irritation. pH: 4.2 (0.2 M solution)

Respiratory : Not classified

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

Reproductive toxicity : Not classified.

Specific target organ toxicity : May cause respiratory irritation.

Specific target organ toxicity : Not classified.

Aspiration hazard : Not classified.

## Ecological Information: Toxicity

Ecotoxicity:	
EPA Ecological Toxicity rating:	Slightly toxic to practically non-toxic to aquatic organisms based on the Federal Insecticide Fungicide and Rodenticide Act (FIFRA) acute toxicity ratings.
Acute Toxicity to Fish:	(Oncorhynchus mykiss) 96 hr: LC <sub>50</sub> = > 95.9 mg/L



Chronic Toxicity to Fish:	No data available
Acute Toxicity to Aquatic Invertabrates:	No data available
Chronic Toxicity to Aquatic Invertabrates:	No data available
Toxicity to Aquatic Plants:	No data available
Toxicity to Bacteria:	No data available
Toxicity to Soil Dwelling Organisms:	No data available
Toxicity to Terrestrial Plants:	No data available
<b>Enviromental Fate:</b>	
Stability in water:	Stable
Stability in soil:	Stable
Transport and Distribution:	Calculated, fugacity level III: $3.98 \times 10^{-12}$ to air, 45.3% to water, 54.6% to soil, 0.0755% to sediment. Phosphates, whether water or citrate soluble, are translocated in the soil only over very short period and are them immobilized.
Toxicity: Inorganic phosphates have the potential to increase the growth of freshwater algae, whose eventual death will.	
<b>Degradation Products:</b>	
Biodegradation:	The Phosphorus cycle is well understood. Phosphates are converted to calcium or iron/aluminum phosphates or are incorporated with the organic soil matter.
Photodegradation:	No data available.

#### **V. Ingredient: Duration-45**

Product Name	:	<b>Duration CR ® urea</b>
Product Code	:	KAS_DURATION_US_EN
Physical State	:	Solid
Form	:	Granular solid
Color	:	Light brown to tan
Odor	:	Slightly ammoniacal
Chemical Family	:	Modified Urea Polymer
Reactivity	:	The product is non-reactive under normal conditions of use, storage, and transport
Chemical Stability	:	Stable under normal temperature conditions

Possibility of Hazardous Reactions : Hazardous reactions do not occur

Conditions to Avoid : Heat. Extreme temperatures.

Incompatible Materials : Strong oxidizing agents. Acids. Alkalis.

Hazardous Decomposition Products : Ammonia. Carbon Oxides. Nitrogen oxides (Nox)

Reactivity : Reacts violently with strong oxidants, nitrates, inorganic chlorides, chlorites, and perchlorates causing fire and explosion hazard.

Chemical Stability : Normally stable. May gradually give off ammonia. The product is hygroscopic and will absorb water by contact with the moisture in the air.

Possibility of hazard reactions: Hazardous polymerization does not occur.

Conditions to avoid : Moisture; High temperatures; Contact with incompatible materials.

Incompatible materials : Strong oxidizing agents; Nitric acid; Nitrites

Hazard decomposition products: Carbon oxides; Nitrogen oxides (Nox); Ammonia; Biuret

**Toxicological Information:**

Inhalation : high concentrations of dust may irritate throat and respiratory system and cause coughing

Skin contact : dust may irritate skin

Eye contact : dust may irritate eyes

Ingestion : may cause discomfort if swallowed

Symptoms : irritation, redness, scratching of the cornea, and tearing

Acute toxicity : may cause discomfort if swallowed

Components	Species	Test Results
Urea (CAS # 57-13-6) Acute; oral; LD50	Rat	14300mg/kg

Skin corrosion/irritation : may cause irritation through mechanical abrasion

Serious eye damage : may cause irritation through mechanical abrasion

Respiratory/skin sensitization:

Respiratory sensitization : based on available data, the classification criteria are not met.

Skin sensitization : not a skin sensitizer  
 Germ cell mutagenicity : Based on available data, the classification criteria are not met.  
 Carcinogenicity : This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Reproductive toxicity : Based on available data, the classification criteria is not met.  
 Specific target organ toxicity : Based on available data, the classification criteria is not met.  
 Aspiration hazard : Not an aspiration hazard  
 Chronic effects : Frequent inhalation of dust over a long period of time increases the risk of developing lung diseases.  
 Further info : No other specific acute or chronic health impact noted.

**Ecological Information:**

Components	Species	Test Results
Urea (CAS # 57-13-6) Aquatic Fish; LC50	Leuciscus idus	>6810 mg/l, 96 hours

Persistence and degradability: No data available

Bioaccumulative : No data available

Partition coefficient n-octanol/water (log Kow)

Urea (CAS # 57-13-6)

Mobility in soil : This product is water soluble and may disperse in soil.

**VI. Ingredient: Urea**

Product Name : **Urea, Dry**  
 Product Code : URGRAN  
 Product Form : Mixture  
 Product Group : Commercial product  
 Synonyms : Urea Granular; Urea Microprills; Urea Pastille; Urea Prills  
 Physical State : Solid  
 Appearance : Granules  
 Colour : White  
 Odour : Slight Ammonia  
 pH : 7.2 at 100g/l  
 Molecular weight : 60.07

Melting Point	:	Decomposes above 132.6 °C (270.7 °F)
Vapour Pressure	:	80 Pa at 20°C
Flammability	:	Non-flammable
Density	:	2.31 g/cm <sup>3</sup>
Bulk Density	:	44-49 lb/ft <sup>3</sup> 750 kg/m <sup>3</sup>
Solubility	:	1,193 g/l at 25°C
Log Pow	:	-1.59 @ 20°C

#### GHS-US Classification

Skin Irritation 2 H315

Eye Irritation 2A H319

STOT SE 3 H335

#### Hazard Statements (GHS-US)

H315 – Causes skin irritation

H319 – Causes serious eye irritation

H335 – May cause respiratory irritation

#### Precautionary Statements (GHS-US)

P261 – Avoid breathing dust

P264 – Wash hands thoroughly after handling

P271 – Use only outdoors or in a well-ventilated area

P280 – Wear eye protection, protective gloves, protective clothing

P302+P352 – If on skin: wash with plenty of water

P304+P340 – If inhaled: remove victim to fresh air and keep at rest in a position comfortable for breathing.

P305+P351+P338 – If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P312 – Call a POISON CENTER or doctor/physician if you feel unwell

P332+P313 – If skin irritation occurs: Get medical advice/attention

P337+P313 – If eye irritation persists: Get medical advice/attention

P362 – Take off contaminated clothing

P403+P233 – Store in a well-ventilated place. Keep container tightly closed

P405 – Store locked up

P501 – Dispose of contents/container in accordance with local regional, national, and international

regulations.

- Other Hazards : Hazardous to the aquatic environment
- Reactivity : Stable at ambient temperature and under normal conditions of use
- Chemical Stability : Stable at standard temperature and pressure
- Possibility of hazardous : Hazardous polymerization will not occur.
- Conditions to avoid : Protect from moisture. May slowly hydrolyze to ammonium carbamate and eventually decompose to ammonia and carbon dioxide.
- Incompatible materials : May form explosive mixture if in contact with strong acid such as nitric or perchloric acids. Avoid contact with: strong oxidizers; strong acids or bases; nitrates; hypochlorites. Reacts with sodium or calcium hypochlorite to form explosive nitrogen trichloride.
- Fire Hazard : Decomposes above 132.6°C (270.7°F). Under conditions of fire this material may produce: Ammonia, Nitrogen oxides, and/or Biuret. Short-term exposures to smoke and gases may lead to irreversible lung injury without early signs and symptoms.
- Explosion Hazard : Product is not explosive. May form explosive mixtures if mixed with strong acid (Nitric/Perchloric) and strong oxidizers.
- General Measures : Handle in accordance with good industrial hygiene/safety practice.
- Signal Word : Warning
- Aquatic Environment Hazard: Per OSHA 29 CFR 1910.1200(b)(5)(iii) labelling is not required for URPRLMIF or URPRLCF as labelling is covered under the requirements of the Food and Drug Administration (FDA) of the US Department of Agriculture (USDA).

Name	Product Identifier	% by Weight	GHS-US classification
Urea (Carbamide, Carbonyldiamide, Carbamidic Acid)	(CAS No.) 57-13-6	97.5 – 99.7	Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H335
Alkalinity, as Ammonia		150 ppm (max)	
Methylenediurea	(CAS No.) 13547-17-6	0 – 2.5	Eye Irrit. 2A, H319
Biuret	(CAS No.) 108-19-0	0 – 1.5	Skin Irrit. 2, H315 Eye Irrit. 2A, H319

Control Parameters:

Urea (57-13-6)

USA ACGIH (nuisance dust)	ACGIH TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> – inhalation particulate
USA OSHA (nuisance dust)	OSHA PEL (TWA) (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup> – Respirable (particulate) Fraction: Urea

**Toxicological Information**

Acute Toxicity : Not classified

LD50 Oral Rat	8471 mg/kg
LD50 Oral Rat	14,300 mg/kg-male; 15,000 mg/kg-female
LD50 Oral Mouse	11,500 mg/kg-male; 13,000 mg/kg-female

Skin corrosion/irritation : Causes skin irritation

Serious eye damage/irritation: Causes eye irritation

Respiratory or skin sensitisation : Not classified

Germ cell mutagenicity : Bacterial Genetic Toxicity Invitro:  
Gene Mutation:  
Salmonella typhimurium – Bacterial reverse mutation assay:  
Negative Chinese Hamster - Chromosomal aberration test:  
Positive (very high dose); Mouse: Positive (very high dose). Non-Bacterial Genetic Toxicity In-Vitro: Chromosomal Aberration:  
Mouse – Bone Marrow Cytogenetic test: Positive (extremely high dose).

Carcinogenicity : Not listed in IARC Monographs, by NTP or OSHA

Reproductive Toxicity : Toxicity to Reproductive:  
No toxic affects on mouse gonads up to 6,750 mg/kg/day.  
No toxic affects on rat gonads up to 2,250 mg/kg/day.  
Developmental toxicity/ Teratogenicity: Not teratogenic.

Specific target organ toxicity (single exposure) : May cause respiratory irritation.

Specific target organ toxicity (repeated exposure) : Not Classified

Aspiration hazard : Not Classified

**Ecological Informations**

Ecotoxicity	Acute Toxicity to Fish:	96 -h: (Barillius barna)
	Chronic Toxicity to Fish:	LC <sub>50</sub> =>9,000mg/L
	Acute Toxicity to Aquatic Invertebrates:	No data available
	Toxicity to Aquatic Plants:	(Daphnia magna): 24-h EC <sub>50</sub> : > 10,000 mg/L
	Toxicity to Bacteria:	(Scenedesmus quadricauda)
	Toxicity to Soil Dwelling Organisms:	192-hr cell multiplication inhibition test-TT>10,000 mg/L
	Toxicity to Other Non Mammalian Terrestrial Species:	No data available
	Toxicity to Terrestrial Plants:	Applications of nitrogenous fertilizers to grassland for long periods of time may have deleterious effects on earthworms in the absence of liminig.
	Stability in Water:	(Pigeon) – Subcutaneous – LDLO = 16,000 mg/kg. Since Urea is a fertilizer, it may promote eutrophication in waterways. Non-toxic to aquatic organisms as defined by USEPA.
		7 days exposure to 0mg urea / leaf-tip necrosis
	T <sub>1/2</sub> > 1 year	
Environmental Fate:	Stability in Soil:	No data available

Toxicity:	Transport and Distribution: Non-toxic to aquatic organisms as defined by USEPA. No know toxicity.	.16% in air; 99.84% in water (calculated (Fugacity Level 1))
Degradation Products:	Biodegradation: Photodegradation:	Ultimety biodegradable (OECDTG 302B) 93-98% (SCAS 24 hr) No data available.

**Enviromental Precautions**

If spill could potentially enter any waterway, including intermittent dry creeks, contact the U.S. Coast Guard National Response Center at 800-424-8802. In case of accident or road spill notify CHEMTREC at 800-424-9300.

**Containment and Cleaning Up**

If contaminated with other materials, contain and collect as any solid in suitable containers. Do not allow into drains or water courses or dispose of where ground or surface waters may be affected.

Prevent large quantities from contacting vegetation.

Recover the product by vacuuming, shoveling, or sweeping and place in appropriate container to be disposed at an appropriate disposal facility according to current applicable laws and regulations and product characteristics at the time of disposal. Provide adequate ventilation. Avoid generation of dust during clean-up of spills. If uncontaminated, recover, reuse product.

Practice food housekeeping – spillage can be slippert on smooth surface either wet or dry.

**Transport Information**

- UN number : No dangerous good in sense of transport regulations.
- UN proper shipping name : Not applicable
- Additional Information : No supplemetary information available.
- Overland transport : No additional information.
- Transport by sea : No additional information.
- Air transport : No additional information availiable.

**Regulatory Information**

**US Federal Regulations**

Urea, Dry



SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard
-------------------------------------	---------------------------------

Urea (57-13-6)
Listed on the United States TSCA (Toxic Substances Control Act) inventory

Biuret (108-19-0)
Listed on the United States TSCA (Toxic Substances Control Act) inventory

**US State Regulations**

The following states have an OSH program approved by OSHA. If you are located in any of these states you may be under state jurisdiction rather than federal jurisdiction and your state may have more stringent requirements than OSHA. You should consult your state regulations to ensure compliance.

- |              |          |             |                |                 |
|--------------|----------|-------------|----------------|-----------------|
| Alaska       | Indiana  | Minnesota   | North Carolina | Utah            |
| Arizona      | Iowa     | Nevada      | Oregon         | Vermont         |
| California   | Kentucky | New Mexico  | Puerto Rico    | *Virgin Islands |
| *Connecticut | Maryland | *New Jersey | South Carolina | Virginia        |
| Hawaii       | Michigan | *New York   | Tennessee      | Washington      |
| *Illinois    |          |             |                | Wyoming         |

\*The state plans in these states apply only to public sector employers. In these states private sector employers are subject to USOL – OSHA jurisdiction. All other state plans apply to both public and private sector employers.

Urea (57-13-6)
US – Minnesota – Hazardous Substance List
US – Texas – Effects Screening Levels – Long term/Short term

**Other Information**

- NFPA health hazard : 2 – Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt medical attention is given.
- NFPA fire hazard : 0 – Materials that will not burn.
- NFPA reactivity : 0 – Normally stable, even under fire exposure conditions, and are not reactive with water.

Skin Irrit. 2	Skin corrosion/irritation Category 2
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H315	Causes skin irritation
H319	Causes serious eye irritation
H335	May cause respiratory irritation

### VII. Ingredient: Dolomite Lime

Product Name	:	<b>Dolomite Lime</b>
Recommended Use	:	Mineral filler, fluxing agent in steel and glass manufacturing
Signal Word	:	Danger
Hazard Statements	:	May cause cancer. May cause damage to organs (lungs) through prolonged or repeated exposure. Products designated 6x16, 10, 11P, 12, 17, or 20 – when shipped in bulk – may be hot (up to 250°F) at the time of shipment.
NFPA Hazard Class	Health:1	Flammability:0
		Reactivity:0
HMIS Hazard Class	Health:1	Flammability:0
		Reactivity:0
Appearance	:	Angular gray, white, and tan solid particles ranging in size from powder to boulders.
Odor	:	No odor
Vapor pressure	:	Not applicable
Odor threshold	:	Not applicable
Vapor density	:	Not applicable
pH	:	9.4 in saturated water solution
Relative density	:	Specific gravity = 2.7 – 2.9
Melting/Freezing point	:	Not applicable
Solubility	:	Negligible in water
Flash point	:	None
Evaporation rate	:	None
Flammability	:	Non flammable
Auto ignition temperature	:	Non flammable
Decomposition temperature	:	When heated at 1100 – 1700°F, dolomitic limestone decomposes

into dolomitic quicklime releasing carbon dioxide gas.

- Viscosity : Not applicable.
- Reactivity : The product is stable and non-reactive under normal conditions of use, storage and transport.
- Stability : Reacts with acids evolving CO<sub>2</sub>. Stable if no acids or strong oxidizing agents are present.
- Hazardous polymerization : Will not occur.
- Incompatibility : Ignites on contact with fluorine and other strong oxidizing agents and is incompatible with acids, ammonium salts, and magnesium metal. May cause pitting of aluminum.

**Cleanup Procedures:** Spilled materials, where dust is generated, may overexpose clean-up personnel to respirable dust. Use of respiratory protective equipment may be necessary. Do not dry sweep or use compressed air for clean-up. Dolomitic limestone may be wetted with water to control dusting. Prevent spilled materials from entering streams, drains, or sewers. Waste disposal method: pick up and reuse clean materials. Dispose of waste materials only in accordance with applicable federal, state, and local laws and regulations.

**Recommendations on the conditions for safe storage:** May cause pitting of aluminum. Ignites on contact with fluorine and other strong oxidizing agents and is incompatible with acids, ammonium salts, and magnesium metal.

Selected Occupational Exposure Limits (effective, June 1, 2015)

1 – Value equivalent to OSHA formulas (29 CFR 1910.1000) and MSHA Metal/Non-Metal (1973 TVLs at 30 CFR 56/57 .5001)

2 – Value also applies to MSHA Metal/Non-Metal (1973 TVLs at 30 CFR 56/57 .5001)

3 – OSHA enforces 0.250 mg/m<sup>3</sup> in construction and shipyards (CPL-03-00-007).

4 – Value also applies to OSHA construction (29 CFR 1926.55, Appendix A) and shipyards (CPL-03-00-007).

5 – MSHA limit = 10 mg/m<sup>3</sup>.

6 – Value also applies to shipyards (29 CFR 1915), marine terminals (29 CFR 1917), and longshoring (29 Cfr 1918).

**US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)**

Components	Type	Value	Form
------------	------	-------	------

Particulates not otherwise classified (CAS SEQ250)	PEL	5 mg/m <sup>3</sup> 15mg/m <sup>3</sup>	Respirable Fraction Total Dust
Calcium Carbonate (CAS 1317-65-3)	TWA	5mg/m <sup>3</sup> 15mg/m <sup>3</sup>	Respirable Fraction 6 Total Dust 5,6

**US. OSHA Table Z-3 (29 CFR 1910.1000)**

Components	Type	Value	Form
Crystalline Silica (Quartz) (CAS 14808-60-7)	TWA	0.3 mg/m <sup>3</sup> 0.1 mg/m <sup>3</sup> 2.4 mppcf	Total Dust. 1,2,3 Respirable. 1,2,3 Respirable. 1,2,3
Particulates not otherwise classified (CAS SEQ250)	TWA	5 mg/m <sup>3</sup> 15mg/m <sup>3</sup> 50 mppcf 15 mppcf	Respirable fraction. 1 Total Dust. 1,4,5 Total Dust. 1,4 Respirable fraction. 1
Tridymite and Cristobalite (other forms of crystalline silica) (CAS Mixture)	TWA	0.15 mg/m <sup>3</sup> 0.05mg/m <sup>3</sup> 1.2 mppcf	Total Dust. 1 Respirable. 1 Respirable. 1

**US. Acgih Threshold Limit Values**

Components	Type	Value	Form
Crystalline Silica (CAS 14808-60-7)	TWA	0.025 mg/m <sup>3</sup>	Respirable Fraction
Tridymite and Cristobalite (other forms of crystalline silica) (CAS Mixture)	TWA	0.025 mg/m <sup>3</sup>	Respirable Fraction

**US. NIOSH: Pocket Guide to Chemical Hazards**

Components	Type	Value	Form
Crystalline Silica (CAS	TWA	0.05 mg/m <sup>3</sup>	Respirable dust

14808-60-7)			
Calcium Carbonate (CAS 1317-65-3	TWA	5 mg/m3 10 mg/m3	Respirable fraction. Total dust.

**Exposure Guidelines:** OSHA PELs, MSHA PELs, and ACGIH TLVs and 8-hr TWA values. NIOSH RELs are for TWA exposures up to 10 hr/day and 40-hr/wk. Occupational exposure to nuisance dust (total and respirable) and respirable crystalline silica should be monitored and controlled. Terms including “Particulates Not Otherwise Classified”, “Particulates Not Otherwise Regulated”, “Particulates Not Otherwise Specified”, and “Inert or Nuisance Dust” are often used interchangeably; however, the user should review each agency's terminology for differences in meanings.

#### Toxicological Information

**Inhalation:** Repeated inhalation of respirable crystalline silica (quartz) may cause silicosis, a fibrosis (scarring) of the lungs. Silicosis is irreversible and may be fatal. Silicosis increases the risk of contracting pulmonary tuberculosis. Some studies suggest that repeated inhalation or respirable crystalline silica may cause other adverse health effects including lung and kidney cancer.

**Skin contact:** Limestone dust: May cause irritation through mechanical abrasion.

**Eye contact:** Limestone dust: May cause irritation through mechanical abrasion.

**Ingestion:** Not likely, due to the form of the product. However, accidental ingestion of the content may cause discomfort.

**Symptoms related to the physical, chemical, and toxicological characteristics:** Limestone dust:

Discomfort in the chest. Shortness of breath. Coughing.

#### Information on toxicological effects:

Acute toxicity	:	Not expected to be acutely toxic.
Skin corrosion/irritation	:	This product is not expected to be a skin hazard.
Serious eye damage and eye irritation:	:	Direct contact with eyes may cause temporary irritation.
Respiratory or skin sensitization	:	No respiratory sensitizing effects known.
Skin Sensitization	:	Not known to be dermal irritant or sensitizer.
Germ cell mutagenicity	:	than 0.1% are mutagenic or genotoxic.
Carcinogenicity	:	Respirable crystalline silica has been classified by IARC and NTP as a known human carcinogen, and classified by ACGIH as a suspected human carcinogen.

Aspiration hazard	:	Due to the physical form of the product it is not an aspiration hazard.
Chronic effects	:	Prolonged inhalation of respirable crystalline silica may be harmful. May cause damage to organs (lungs) through prolonged or repeated exposure. There are reports in the literature suggesting that excessive crystalline silica exposure may be associated with autoimmune disorders and other adverse health effects involving the kidney. In particular, the incidence of scleroderma (thickening of the skin caused by swelling and thickening of fibrous tissue) appears to be higher in silicotic individuals. To date, the evidence does not conclusively determine a causal relationship between silica exposure and these adverse health effects.

**Ecotoxicity:** Not expected to be harmful to aquatic organisms. Discharging limestone dust and fines into waters may increase total suspended particulate (TSP) levels that can be harmful to certain aquatic organisms.

**Other adverse effects:** No other adverse environmental effects (e.g., ozone depletion, photochemical ozone creation potential, global warming potential) are expected from this component.

US Federal Regulations: This product is a “Hazard Chemical” as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D) – Not Regulated

U.S. TSCA Inventory List. All Chemical ingredients are listed.

RCRA Hazardous Waste Number: Not listed (40 CFR 261.33)

RCRA Hazardous Waste Classification (40 CFR 261): Not Classified

CERCLA Hazardous Substance List (40 CFR 302.4) Not Listed

CERCLA Reportable Quantity (RQ): not listed

SARA Hazard categories

Immediate hazard – no

Delayed hazard – yes

Fire hazard – no

Pressure hazard – no

Reactivity hazard – no

SARA311/312 Hazardous Chemical : yes SARA 313 (TRI Reporting) – Not Regulated

SARA Toxic Chemical (40 CFR 372.65): not listed

SARA 302 (Extremely Hazardous Substance): not listed

OSHA – Air contaminant (29 CFR 1910.1000, Table Z-1, Z-1-A)

Specifically Regulated Substance (29 CFR 1910): not listed

MSHA – not listed

Clean Air Act (CAA) Section 112 – Hazardous Air Pollutants (HAP's) List – Not Regulated

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130) – Not Regulated

Safe Drinking Water Act (SDWA) – Not Regulated

### **VIII. Other Hazard Information**

#### **Environmental Protection:**

**Appropriate engineering controls:** Use ventilation and dust collection to control exposure to below applicable limits.

**Recommendations for personal protective measures:** Respirable dust and quartz levels should be monitored regularly to determine worker exposure levels. Exposure levels in excess of allowable exposure limits should be reduced by all feasible engineering controls including (but not limited to) wet suppression, ventilation, process enclosure, and enclosed employee workstations.

Any special requirements for PPE:

Eye protection: Safety glasses with side shields should be worn as minimum protection. Dust goggles should be worn when excessively (visibly) dusty conditions are present or anticipated.

Skin protection: Use gloves to provide hand protection from abrasion. In dusty conditions wear long sleeve shirt. Wash work clothes after each use.

Respiratory Protection: All respirators must be NIOSH-approved for the exposure levels present. (See NIOSH Respirator Selection Guide). The need for respiratory protection should be evaluated by a qualified safety and health professional. Activities that generate dust require the use of an appropriate dust respirator where dust levels exceed or are likely to exceed allowable exposure limits. For respirable silica levels that exceed or are likely to exceed an 8 hr Time Weighted Average (TWA) of 0.5 mg/m<sup>3</sup>, a high efficiency particulate filter respirator must be worn at a minimum; however, if respirable silica levels exceed or are likely to exceed an 8 hr TWA of 5.0 mg/m<sup>3</sup> a positive pressure, full face respirator or equivalent is required. Respirator use must comply with applicable MSHA (42 CFR 84) or OSHA (29 CFR 1910.134) standards, which include provisions for a user training program, respirator inspection, repair and cleaning, respirator fit testing, medical surveillance and other requirements.

#### **Disposal Information:**

Disposal instructions: Do not allow this material to drain into sewers/water supplies. Dispose in

accordance with all applicable regulations.

Hazardous waste code: Not regulated

Waste from residues: Disposal recommendations are based on the material as supplied. Disposal must be in accordance with current applicable laws and regulations, and material characteristics at time of disposal.

Contaminated packaging: Since emptied containers may retain product residue, follow label warnings even after container is emptied.

**Transport Information:**

DOT – not regulated as dangerous goods.

IATA – not regulated as dangerous goods.

IMDG – not regulated as dangerous goods.

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code** – not applicable. However, the product is covered under Appendix I of the IMSBC Code.

**Regulatory Information:**

US federal regulations: This product is not known to be a “Hazardous Chemical” as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200. All components are listed on or exempt from the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D) – not regulated

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) – not listed

CERCLA Hazardous Substance List (40 CFR 302.4) – not listed

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Immediate hazard – no

Delayed hazard – no

Fire hazard – no

Pressure hazard – no

Reactivity hazard – no

SARA 302 Extremely hazardous substance – not listed

SARA 311/312 Hazardous chemical – no

SARA 313 (TRI reporting) – not regulated

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List – not regulated

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130) – not regulated

Safe Drinking Water Act – not regulated

Food and Drug – total food additive

Administration (FDA) – direct food additive; GRAS food additive



**Other Information:**

Further information: HMIS is registered trade and service mark of the NPCA. A HMIS Health rating including an \* indicates a chronic hazard.

HMIS ratings: Health: 1

Flammability: 0

Physical Hazard: 0

Abbreviations: LC50: Lethal Concentration, 50%; LD50: Lethal Dose, 50%

**IX. Conditions of Sale and Warranty**

The directions of use for this product reflect the opinion of experts based on field use and tests. The directions are believed to be reliable and should be followed carefully. However, it is impossible to eliminate all risks inherently associated with use of this product. Crop injury, ineffectiveness, or other unintended consequences may result because of such factors as weather conditions, presence of other materials, or the manner of use or application all of which are beyond the control of Groenink's Elevator and Hardware, Inc. or the Seller. All such risks shall be assumed by the Buyer. Groenink's Elevator and Hardware, Inc. warrants that this product conforms to the chemical description on the label and is reasonably fit for the purposes referred to in its Direction for Use subject to the inherent risks referred to above. **Groenink's Elevator and Hardware, Inc USA makes no other express or implied Warranty of Fitness or Merchantability or any other express or implied warranty. In no case shall Groenink's Elevator and Hardware, Inc. or the Seller be liable for consequential, special, or indirect damages resulting from the use or handling of this Product.** Groenink's Elevator and Hardware, Inc. and the Seller offer this product, and the Buyer and user except it, subject to the foregoing Conditions of Sale and Warranty, which may be varied only by agreement in writing