

GROENINK'S
MATERIAL AND DATA SHEET
GET A GRIP

Date Prepared: 2/13/16

I. Product Identity

PRODUCT NAME: 42-0-0 40% Nitroform

MFR INFO: Groenink's Elevator and Hardware
11260 Michigan Ave.
Nunica, MI 49448

FOR EMERGENCY: (800) 424-9300 (CHEMTREC)
FOR INFORMATION: (616) 837-7391

CURRENT AS OF: 3/26/16

II. Ingredient List

Urea
Nitroform

III. Ingredient: Urea

Product Name	:	Urea, Dry
Product Code	:	URGRAN
Product Form	:	Mixture
Product Group	:	Commercial product
Synonyms	:	Urea Granular; Urea Microprills; Urea Pastille; Urea Prills
Physical State	:	Solid
Appearance	:	Granules
Colour	:	White
Odour	:	Slight Ammonia
pH	:	7.2 at 100g/l
Molecular weight	:	60.07
Melting Point	:	Decomposes above 132.6 °C (270.7 °F)
Vapour Pressure	:	80 Pa at 20°C
Flammability	:	Non-flammable
Density	:	2.31 g/cm ³
Bulk Density	:	44-49 lb/ft ³ 750 kg/m ³

Solubility : 1,193 g/l at 25°C

Log Pow : -1.59 @ 20°C

GHS-US Classification

Skin Irritation 2 H315

Eye Irritation 2A H319

STOT SE 3 H335

Hazard Statements (GHS-US)

H315 – Causes skin irritation

H319 – Causes serious eye irritation

H335 – May cause respiratory irritation

Precautionary Statements (GHS-US)

P261 – Avoid breathing dust

P264 – Wash hands thoroughly after handling

P271 – Use only outdoors or in a well-ventilated area

P280 – Wear eye protection, protective gloves, protective clothing

P302+P352 – If on skin: wash with plenty of water

P304+P340 – If inhaled: remove victim to fresh air and keep at rest in a position comfortable for breathing.

P305+P351+P338 – If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P312 – Call a POISON CENTER or doctor/physician if you feel unwell

P332+P313 – If skin irritation occurs: Get medical advice/attention

P337+P313 – If eye irritation persists: Get medical advice/attention

P362 – Take off contaminated clothing

P403+P233 – Store in a well-ventilated place. Keep container tightly closed

P405 – Store locked up

P501 – Dispose of contents/container in accordance with local regional, national, and international regulations.

Other Hazards : Hazardous to the aquatic environment

Reactivity : Stable at ambient temperature and under normal conditions of use

Chemical Stability : Stable at standard temperature and pressure

Possibility of hazardous : Hazardous polymerization will not occur.

Conditions to avoid : Protect from moisture. May slowly hydrolyze to ammonium

carbamate and eventually decompose to ammonia and carbon dioxide.

- Incompatible materials : May form explosive mixture if in contact with strong acid such as nitric or perchloric acids. Avoid contact with: strong oxidizers; strong acids or bases; nitrates; hypochlorites. Reacts with sodium or calcium hypochlorite to form explosive nitrogen trichloride.
- Fire Hazard : Decomposes above 132.6°C (270.7°F). Under conditions of fire this material may produce: Ammonia, Nitrogen oxides, and/or Biuret. Short-term exposures to smoke and gases may lead to irreversible lung injury without early signs and symptoms.
- Explosion Hazard : Product is not explosive. May form explosive mixtures if mixed with strong acid (Nitric/Perchloric) and strong oxidizers.
- General Measures : Handle in accordance with good industrial hygiene/safety practice.
- Signal Word : Warning
- Aquatic Environment Hazard: Per OSHA 29 CFR 1910.1200(b)(5)(iii) labelling is not required for URPRLMIF or URPRLCF as labelling is covered under the requirements of the Food and Drug Administration (FDA) of the US Department of Agriculture (USDA).

Name	Product Identifier	% by Weight	GHS-US classification
Urea (Carbamide, Carbonyldiamide, Carbamidic Acid)	(CAS No.) 57-13-6	97.5 – 99.7	Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H335
Alkalinity, as Ammonia		150 ppm (max)	
Methylenediurea	(CAS No.) 13547-17-6	0 – 2.5	Eye Irrit. 2A, H319
Biuret	(CAS No.) 108-19-0	0 – 1.5	Skin Irrit. 2, H315 Eye Irrit. 2A, H319

Control Parameters:

Urea (57-13-6)		
USA ACGIH (nuisance dust)	ACGIH TWA (mg/m ³)	10 mg/m ³ – inhalation particulate
USA OSHA (nuisance dust)	OSHA PEL (TWA) (mg/m ³)	5 mg/m ³ – Respirable (particulate) Fraction: Urea

Toxicological Information

Acute Toxicity : Not classified

LD50 Oral Rat	8471 mg/kg
---------------	------------

LD50 Oral Rat	14,300 mg/kg-male; 15,000 mg/kg-female
LD50 Oral Mouse	11,500 mg/kg-male; 13,000 mg/kg-female

Skin corrosion/irritation : Causes skin irritation

Serious eye damage/irritation: Causes eye irritation

Respiratory or skin : Not classified

sensitisation

Germ cell mutagenicity : Bacterial Genetic Toxicity Invitro:
Gene Mutation:
Salmonella typhimurium – Bacterial reverse mutation assay:
Negative Chinese Hamster - Chromosomal aberration test:
Positive (very high dose); Mouse: Positive (very high dose). Non-
Bacterial Genetic Toxicity In-Vitro: Chromosomal Aberration:
Mouse – Bone Marrow Cytogenetic test: Positive (extremely high dose).

Carcinogenicity : Not listed in IARC Monographs, by NTP or OSHA

Reproductive Toxicity : Toxicity to Reproductive:
No toxic affects on mouse gonads up to 6,750 mg/kg/day.
No toxic affects on rat gonads up to 2,250 mg/kg/day.
Developmental toxicity/ Teratogenicity: Not teratogenic.

Specific target organ : May cause respiratory irritation.
toxicity (single exposure)

Specific target organ : Not Classified
toxicity (repeated exposure)

Aspiration hazard : Not Classified

Ecological Informations

Ecotoxicity	Acute Toxicity to Fish:	96 -h: (Barillius barna)
	Chronic Toxicity to Fish:	LC ₅₀ =>9,000mg/L
	Acute Toxicity to Aquatic Invertebrates:	No data available
	Toxicity to Aquatic Plants:	(Daphnia magna): 24-h EC ₅₀ : > 10,000 mg/L

	<p>Toxicity to Bacteria:</p> <p>Toxicity to Soil Dwelling Organisms:</p> <p>Toxicity to Other Non Mammalian Terrestrial Species:</p> <p>Toxicity to Terrestrial Plants:</p> <p>Stability in Water:</p>	<p>(Scenedesmus quadricauda) 192-hr cell multiplication inhibition test-TT>10,000 mg/L</p> <p>No data available</p> <p>Applications of nitrogenous fertilizers to grassland for long periods of time may have deleterious effects on earthworms in the absence of liminig.</p> <p>(Pigeon) – Subcutaneous – LDLO = 16,000 mg/kg. Since Urea is a fertilizer, it may promote eutrophication in waterways. Non-toxic to aquatic organisms as defined by USEPA.</p> <p>7 days exposure to 0mg urea / leaf-tip necrosis</p> <p>T_{1/2} > 1 year</p>
Environmental Fate:	Stability in Soil:	No data available
Toxicity:	Transport and Distribution: Non-toxic to aquatic organisms as defined by USEPA. No know toxicity.	.16% in air; 99.84% in water (calculated (Fugacity Level 1))
Degradation Products:	Biodegradation: Photodegradation:	Ultimately biodegradable (OECDTG 302B) 93-98%

(SCAS 24 hr) No data available.

Environmental Precautions

If spill could potentially enter any waterway, including intermittent dry creeks, contact the U.S. Coast Guard National Response Center at 800-424-8802. In case of accident or road spill notify CHEMTREC at 800-424-9300.

Containment and Cleaning Up

If contaminated with other materials, contain and collect as any solid in suitable containers. Do not allow into drains or water courses or dispose of where ground or surface waters may be affected.

Prevent large quantities from contacting vegetation.

Recover the product by vacuuming, shoveling, or sweeping and place in appropriate container to be disposed at an appropriate disposal facility according to current applicable laws and regulations and product characteristics at the time of disposal. Provide adequate ventilation. Avoid generation of dust during clean-up of spills. If uncontaminated, recover, reuse product.

Practice food housekeeping – spillage can be slippert on smooth surface either wet or dry.

Transport Information

UN number : No dangerous good in sense of transport regulations.
UN proper shipping name : Not applicable
Additional Information : No supplementary information available.
Overland transport : No additional information.
Transport by sea : No additional information.
Air transport : No additional information available.

Regulatory Information

US Federal Regulations

Urea, Dry

SARA Section 311/312 Hazard Classes

Immediate (acute) health hazard

Urea (57-13-6)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Biuret (108-19-0)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

US State Regulations

The following states have an OSH program approved by OSHA. If you are located in any of these states you may be under state jurisdiction rather than federal jurisdiction and your state may have more stringent requirements than OSHA. You should consult your state regulations to ensure compliance.

Alaska	Indiana	Minnesota	North Carolina	Utah
Arizona	Iowa	Nevada	Oregon	Vermont
California	Kentucky	New Mexico	Puerto Rico	*Virgin Islands
*Connecticut	Maryland	*New Jersey	South Carolina	Virginia
Hawaii	Michigan	*New York	Tennessee	Washington
*Illinois				Wyoming

*The state plans in these states apply only to public sector employers. In these states private sector employers are subject to USOL – OSHA jurisdiction. All other state plans apply to both public and private sector employers.

Urea (57-13-6)

US – Minnesota – Hazardous Substance List

US – Texas – Effects Screening Levels – Long term/Short term

Other Information

NFPA health hazard : 2 – Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt medical attention is given.

NFPA fire hazard : 0 – Materials that will not burn.

NFPA reactivity : 0 – Normally stable, even under fire exposure conditions, and are not reactive with water.

Skin Irrit. 2	Skin corrosion/irritation Category 2
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H315	Causes skin irritation
H319	Causes serious eye irritation

H335

May cause respiratory irritation

IV. Ingredient: Nitroform

Product Name	:	Nitroform
Product Code	:	KAS_NITROFORM_US_EN
Appearance	:	Blue powder
Physical state	:	Solid
Form	:	Powder and Granular
Color	:	Blue
Chemical Family	:	Modified Urea Polymer
Reactivity	:	The product is non-reactive under normal conditions of use, storage, and transport
Chemical Stability	:	Stable under normal temperature conditions
Possibility of Hazardous Reactions	:	Hazardous reactions do not occur
Conditions to Avoid	:	Heat. Extreme temperatures.
Incompatible Materials	:	Strong oxidizing agents. Acids. Alkalis.
Hazardous Decomposition Products	:	Ammonia. Carbon Oxides. Nitrogen oxides (Nox)

IV. Other Hazard Information

Environmental Protection:

Appropriate engineering controls: Use ventilation and dust collection to control exposure to below applicable limits.

Recommendations for personal protective measures: Respirable dust and quartz levels should be monitored regularly to determine worker exposure levels. Exposure levels in excess of allowable exposure limits should be reduced by all feasible engineering controls including (but not limited to) wet suppression, ventilation, process enclosure, and enclosed employee workstations.

Any special requirements for PPE:

Eye protection: Safety glasses with side shields should be worn as minimum protection. Dust goggles should be worn when excessively (visibly) dusty conditions are present or anticipated.

Skin protection: Use gloves to provide hand protection from abrasion. In dusty conditions wear long sleeve shirt. Wash work clothes after each use.

Respiratory Protection: All respirators must be NIOSH-approved for the exposure levels present. (See NIOSH Respirator Selection Guide). The need for respiratory protection should be evaluated by a qualified safety and health professional. Activities that generate dust require the use of

an appropriate dust respirator where dust levels exceed or are likely to exceed allowable exposure limits. For respirable silica levels that exceed or are likely to exceed an 8 hr Time Weighted Average (TWA) of 0.5 mg/m³, a high efficiency particulate filter respirator must be worn at a minimum; however, if respirable silica levels exceed or are likely to exceed an 8 hr TWA of 5.0 mg/m³ a positive pressure, full face respirator or equivalent is required. Respirator use must comply with applicable MSHA (42 CFR 84) or OSHA (29 CFR 1910.134) standards, which include provisions for a user training program, respirator inspection, repair and cleaning, respirator fit testing, medical surveillance and other requirements.

Disposal Information:

Disposal instructions: Do not allow this material to drain into sewers/water supplies. Dispose in accordance with all applicable regulations.

Hazardous waste code: Not regulated

Waste from residues: Disposal recommendations are based on the material as supplied. Disposal must be in accordance with current applicable laws and regulations, and material characteristics at time of disposal.

Contaminated packaging: Since emptied containers may retain product residue, follow label warnings even after container is emptied.

Transport Information:

DOT – not regulated as dangerous goods.

IATA – not regulated as dangerous goods.

IMDG – not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code – not applicable. However, the product is covered under Appendix I of the IMSBC Code.

Regulatory Information:

US federal regulations: This product is not known to be a “Hazardous Chemical” as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200. All components are listed on or exempt from the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D) – not regulated

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) – not listed

CERCLA Hazardous Substance List (40 CFR 302.4) – not listed

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Immediate hazard – no

Delayed hazard – no

Fire hazard – no

Pressure hazard – no

Reactivity hazard – no

SARA 302 Extremely hazardous substance – not listed

SARA 311/312 Hazardous chemical – no

SARA 313 (TRI reporting) – not regulated

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List – not regulated

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130) – not regulated

Safe Drinking Water Act – not regulated

Food and Drug – total food additive

Administration (FDA) – direct food additive; GRAS food additive

Other Information:

Further information: HMIS is registered trade and service mark of the NPCA. A HMIS Health rating including an * indicates a chronic hazard.

HMIS ratings: Health: 1

Flammability: 0

Physical Hazard: 0

Abbreviations: LC50: Lethal Concentration, 50%; LD50: Lethal Dose, 50%

V. Conditions of Sale and Warranty

The directions of use for this product reflect the opinion of experts based on field use and tests. The directions are believed to be reliable and should be followed carefully. However, it is impossible to eliminate all risks inherently associated with use of this product. Crop injury, ineffectiveness, or other unintended consequences may result because of such factors as weather conditions, presence of other materials, or the manner of use or application all of which are beyond the control of Groenink's Elevator and Hardware, Inc. or the Seller. All such risks shall be assumed by the Buyer. Groenink's Elevator and Hardware, Inc. warrants that this product conforms to the chemical description on the label and is reasonably fit for the purposes referred to in its Direction for Use subject to the inherent risks referred to above. **Groenink's Elevator and Hardware, Inc USA makes no other express or implied Warranty of Fitness or Merchantability or any other express or implied warranty. In no case shall Groenink's Elevator and Hardware, Inc. or the Seller be liable for consequential, special, or indirect damages resulting from the use or handling of this Product.** Groenink's Elevator and Hardware, Inc. and the Seller offer this product, and the Buyer and user except it, subject to the foregoing Conditions of Sale and Warranty, which may be varied only by agreement in writing