

GROENINK'S  
MATERIAL AND DATA SHEET  
GET A GRIP

Date Prepared: 2/13/16

**I. Product Identity**

PRODUCT NAME: 5-24-24

MFR INFO: Groenink's Elevator and Hardware  
11260 Michigan Ave.  
Nunica, MI 49448

FOR EMERGENCY: (800) 424-9300 (CHEMTREC)  
FOR INFORMATION: (616) 837-7391

CURRENT AS OF: 3/19/16

**II. Ingredient List**

Potash  
Monoammonium Phosphate  
Dolomite Lime

**III. Ingredient: Potash**

|                      |   |  |
|----------------------|---|--|
| Product Name         | : | <b>Potash</b>  |
| Product Form         | : | Mixture  |
| Product Code         | : | GRA, SOG, STD, SUS   |
| Other Identification | : | Muriate of Potash: Granular, Standard, and Suspension Grades,<br>WST |
| Use of substance     | : | Fertilizer   |
| Physical state       | : | solid  |
| Appearance           | : | Granular solid. Fine to 4 mm size.                                   |
| Color                | : | White to red   |
| Odour                | : | Slightly oily  |
| Odour threshold      | : | No data available  |
| pH                   | : | 7 (approximately)  |
| Melting point        | : | 771 – 773 °C (1420 – 1423 °F)  |
| Freezing point       | : | No data available  |
| Boiling point        | : | 1420 – 1500 °C (2588 – 2732 °F)                                      |
| Flash point          | : | Not available  |

|                           |   |  |
|---------------------------|---|--|
| Self ignition temperature | : | Not flammable  |
| Decomposition temperature | : | No data available  |
| Flammability              | : | Not flammable  |
| Vapour pressure           | : | 80 Pa at 20°C  |
| Density                   | : | 1.98 g/cc  |
| Solubility                | : | Water: 347 g/l (at 20°C)   |
| Explosive limits          | : | Not explosive  |
| Explosive properties      | : | None known   |
| Oxidizing properties      | : | None known   |
| VOC content               | : | < 0.5 %  |
| Reactivity                | : | Stable at ambient temperature and under normal conditions of use.  |
| Chemical stability        | : | Stable at standard temperature and pressure.   |
| Possibility of hazards    | : | Hazardous polymerization will not occur.   |
| Conditions to avoid       | : | Protect from moisture.   |
| Incompatible materials    | : | Contact with acids liberates toxic gas (chlorine). Contact with hot nitric acid may produce toxic nitrosyl chloride. |
| Hazardous decomposition   | : | Contact with strong acids may produce hydrogen chloride gas.   |

Products

**Firefighting Measures**

|                                  |   |  |
|----------------------------------|---|--|
| Suitable extinguishing media:    | : | Not flammable. Use extinguishing media appropriate for surrounding fire.   |
| Fire hazard                      | : | Under conditions of fire this material may produce: Potassium oxides; Hydrogen chloride; Chlorine gas.                 |
| Explosion hazard                 | : | Product is not explosive.  |
| Reactivity                       | : | Stable at ambient temperature and under normal conditions of use.  |
| Firefighting instructions        | : | Keep upwind. Under conditions of fire this material may produce:<br>Potassium oxides; Hydrogen chloride; Chlorine gas. |
| Protection during fire fighting: | : | Wear full fire-fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA).                            |
| Other Information                | : | Do not allow run off from fire fighting to enter drains or water   |

courses.

### GHS-US classification

Eye Irrit. 2B H320

### GHS-US labelling

Signal word (GHS-US) : Warning

Hazard statements (GHS-US): H320 – Causes eye irritation

Precautionary statements : P264 – Wash hands thoroughly after handling  
P305+P351+P338 – If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P337+P313 – If eye irritation persists: Get medical advice/attention.

### Toxicological Information

Acute toxicity : Not classified

#### Potash

|                        |  |
|------------------------|--|
| Additional information | Potassium chloride is listed by the FDA as “Generally Recognizes as Safe” (GRAS and may be used as a food additive according to prescribed conditions. |
|------------------------|--|

#### Potassium Chloride (7447-40-7)

|               |            |
|---------------|------------|
| LD50 oral rat | 2600 mg/kg |
|---------------|------------|

#### Sodium Chloride (7647-14-5)

|                            |  |
|----------------------------|--|
| LD50 oral rat              | 3 g/kg                                   |
| LD50 dermal rabbit         | > 10 g/kg                                |
| LC50 inhalation rat (mg/l) | > g/m <sup>3</sup> (Exposure time: 1 hr) |

### Ecological Information

#### Ecotoxicity:

|                         |  |
|-------------------------|--|
| Acute toxicity to fish: | (Lepomis macrochirus) (blue gill) – 96 hour – LC <sub>50</sub> = 2010 mg/L (ppm KCl) |
|-------------------------|--|

|  |   |
|--|---|
| Chronic toxicity to fish:                  | No data available   |
| Acute toxicity to aquatic invertebrates:   | (Daphnia magna) – 48 hours – EC <sub>50</sub> – 337 – 825 mg/L; (Physa heterostropha) – 96 hrs – LC <sub>50</sub> = 940 mg/L. |
| Chronic Toxicity to Aquatic Invertebrates: | No data available   |
| Toxicity to aquatic plants:                | ((Nitzshia linearis)diatom) – 5 days – 120 hour TIm = 1,337 ppm KCl; (Scendesmus subspicatus) 72 hour - EC <sub>50</sub>      |
| Toxicity to bacteria: (activated)          | No data available   |
| Toxicity to soil dwelling organisms:       | No data available   |
| Toxicity to terrestrial plants:            | No data available   |

**Enviromental Fate:**

|                             |  |
|-----------------------------|--|
| Stability in Water:         | Ions can persist, dissociates in water   |
| Stability in Soil:          | Binds to clay particles  |
| Transport and Distribution: | 1.51 x 10 <sup>-8</sup> % to air; 45.2% to water; 54.7% to soil; 0.0755% to sediment |

**Toxicity:**

|   |
|---|
| Not toxic to aquatic organisms defined by USEPA |
|---|

**Degration Products:**

|                   |                   |
|-------------------|-------------------|
| Biodegradation:   | No data available |
| Photodegradation: | No data available |

**US State Regulations**

|                                |   |                                 |
|--------------------------------|---|---------------------------------|
| Potash                         | SARA Sectin 311/312   | Immediate (acute) health hazard |
| Potassium Chloride (7447-40-7) | Listed on the United States TSCA (Toxic Substances Control Act) inventory |                                 |

|                             |   |
|-----------------------------|---|
| Sodium Chloride (7647-14-5) | Listed on the United States TSCA (Toxic Substances Control Act) inventory |
|-----------------------------|---|

Full text of H- phrases:

|               |   |
|---------------|---|
| Eye Irrit. 2  | Serious eye damage/eye irritation (Category 2)                |
| Skin Irrit. 2 | Skin corrosion/irritation (Category 2)                        |
| STOT SE 3     | Specific target organ toxicity (single exposure) (Category 3) |
| H315          | Causes skin irritation  |
| H319          | Causes serious eye irritation                                 |
| H335          | May cause respiratory irritation                              |

#### **IV. Ingredient: Monoammonium Phosphate**

Product Form : Substance

Substance Name : **Monoammonium Phosphate (MAP)**

Uses of Substance : Agricultural chemical

GHS-US Classification:

Skin Irrit. 2 H315

Eye Irrit. 2B H320

STOT SE 3 H335

Signal Word : Warning

Engineering Control : Ensure adequate ventilation, especially in confined areas to avoid high dust concentration.

Personal Protection : Gloves, safety glasses, and protective clothing.

Hand Protection : Impermeable protective gloves.

Eye Protection : Protective goggles.

Physical State : Solid

Appearance : Granular solid

Molecular Mass : 115g/mol

Color : Black to green

Odour : Odourless  
 pH : 4.2  
 pH Solution : 0.2 M at 25°C (aqueous solution)  
 Melting Point : 190°C (374°F)  
 Freezing Point : No data available  
 Boiling Point : Decomposes  
 Flash Point : No data available  
 Self Ignition Temperature : Not flammable  
 Flammability : Not flammable  
 Vapour Pressure : < 1mm Hg (at 20°C)  
 Relative Density : No data available  
 Density : 60-64 lbs/ft<sup>3</sup> (loose); 65-72 lbs/ft<sup>3</sup> (tamped)  
 Solubility : Soluble; Water: 328 g/l (at 20°C)  
 Viscosity : No data available

| Name  | Product Identifier  | %   | GHS-US classification                                      |
|---|---------------------|-----|--|
| Monoammonium phosphate as P <sub>2</sub> O <sub>5</sub> | (CAS No.) 7722-76-1 | 52  | Skin Irrit. 2 H315<br>Eye Irrit. 2B H320<br>STOT SE 3 H335 |
| Total Nitrogen, as N***                                 |                     | 11  |  |
| Fluorides, as F   |                     | 0.6 |  |

\*\*\* Product contains monoammonium phosphate as essential ingredient with small amounts of diammonium phosphate, ammonium sulfate, urea, and aluminum/calcium/iron/magnesium phosphate compounds.

| Monoammonium Phosphate (7722-26-1) as P <sub>2</sub> O <sub>5</sub> |                                     |  |
|---|-------------------------------------|--|
| USA ACGIH   | ACGIH TWA (mg/m <sup>3</sup> )      | 10 mg/m <sup>3</sup> – inhalable fraction<br>3 mg/m <sup>3</sup> – respirable fraction |
| USA OSHA  | OSHA PEL (TWA) (mg/m <sup>3</sup> ) | 15 mg/m <sup>3</sup> – particulate<br>3 mg/m <sup>3</sup> - respirable                 |
| Fluorides   |                                     |  |
| USA ACGIH   | ACGIH TWA (mg/m <sup>3</sup> )      | 2.5 mg/m <sup>3</sup>  |
| USA OSHA  | OSHA PEL (TWA) (mg/m <sup>3</sup> ) | 2.5 mg/m <sup>3</sup>  |

Hazard Statements : H315 – Causes skin irritation  
 H320 – Causes eye irritation  
 H335 – May cause respiratory irritation

H401 – Toxic to aquatic life

Precautionary statements : P261 – Avoid breathing dust

P264 – Wash hands thoroughly after handling

P271 – Use only outdoors or in a well-ventilated area

P273 – Avoid release to the environment

P280 – Wear eye protection, face protection, protective clothing, protective gloves

P302+P352 – If on skin, wash with plenty of water

P304+P340 – If inhaled, remove person to fresh air and keep comfortable for breathing

P305+P351+P338 – If in eyes, rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

P312 – Call a Poison Center/ doctor if you feel unwell

P332+P313 – If skin irritation occurs, get medical attention/advice

P337+P313 – If eye irritation persists, get medical attention/advice

P362 – Take off contaminated clothing

P403+P233 – Store in a well-ventilated place. Keep container tightly closed.

P405 – Store locked up

P501 – Dispose of contents/container according to local, regional, national, and international regulations.

### **Stability and Reactivity**

Reactivity – Stable at ambient temperature and under normal conditions of use.

Chemical stability – Stable at standard temperature and pressure.

Possibility of hazardous reactions – Hazardous polymerization will not occur.

Conditions to avoid – Welding or hot work on equipment or plant which may have contained fertilizer should not be done without first washing thoroughly to remove all fertilization.

Incompatible materials – Alkalis and caustic products; strong acids; copper and its alloys.

Hazardous decomposition products – Ammonia is released upon reaction with strong bases or from thermal decomposition.

### **Waste Treatment Methods**

Sewage disposal recommendations – This material is hazardous to the aquatic environment. Keep out of sewers and waterways.

Waste disposal recommendations – place in an appropriate container and dispose of the contaminated material at a licensed site.

Addition information – Dispose of waste material in accordance with all local, regional, national, and international regulations.

### Toxicological Information

|                                    |  |
|------------------------------------|--|
| Monoammonium Phosphate             |  |
| LD50 oral rat                      | > 2000 mg/kg OECD Guideline 425  |
| LD50 dermal rat                    | >5000 mg/kg OECD Guideline 402   |
| Additional information             | This compound is listed by the FDA as generally recognized as safe (GRAS) and may be used as a food additive, for both human food and ruminant feed, according to the prescribed conditions. |
| Monoammonium phosphate (7722-76-1) |  |
| LD50 oral rat                      | 5750 mg/kg   |
| LD50 dermal rabbit                 | > 7940 mg/kg   |

Skin corrosion/irritation : Causes skin irritation. pH: 4.2 (0.2 M solution)

Serious eye damage/irritation: Causes eye irritation. pH: 4.2 (0.2 M solution)

Respiratory : Not classified

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

Reproductive toxicity : Not classified.

Specific target organ toxicity : May cause respiratory irritation.

Specific target organ toxicity : Not classified.

Aspiration hazard : Not classified.

### Ecological Information: Toxicity

|                                 |   |
|---------------------------------|---|
| Ecotoxicity:                    |   |
| EPA Ecological Toxicity rating: | Slightly toxic to practically non-toxic to aquatic organisms based on the Federal Insecticide Fungicide and Rodenticide Act (FIFRA) acute toxicity ratings. |
| Acute Toxicity to Fish:         | (Oncorhynchus mykiss) 96 hr: LC <sub>50</sub> = > 95.9 mg/L   |
| Chronic Toxicity to Fish:       | No data available   |



|  |   |
|--|---|
| Acute Toxicity to Aquatic Invertebrates:   | No data available   |
| Chronic Toxicity to Aquatic Invertebrates:   | No data available   |
| Toxicity to Aquatic Plants:  | No data available   |
| Toxicity to Bacteria:  | No data available   |
| Toxicity to Soil Dwelling Organisms:   | No data available   |
| Toxicity to Terrestrial Plants:  | No data available   |
| <b>Environmental Fate:</b>   |   |
| Stability in water:  | Stable  |
| Stability in soil:   | Stable  |
| Transport and Distribution:  | Calculated, fugacity level III: $3.98 \times 10^{-12}$ to air, 45.3% to water, 54.6% to soil, 0.0755% to sediment. Phosphates, whether water or citrate soluble, are translocated in the soil only over very short period and are them immobilized. |
| Toxicity: Inorganic phosphates have the potential to increase the growth of freshwater algae, whose eventual death will. |   |
| <b>Degradation Products:</b>   |   |
| Biodegradation:  | The Phosphorus cycle is well understood. Phosphates are converted to calcium or iron/aluminum phosphates or are incorporated with the organic soil matter.  |
| Photodegradation:  | No data available.  |

### V. Ingredient: Dolomite Lime

Product Name : **Dolomite Lime**

Recommended Use : Mineral filler, fluxing agent in steel and glass manufacturing

Signal Word : Danger

Hazard Statements : May cause cancer. May cause damage to organs (lungs) through prolonged or repeated exposure. Products designated 6x16, 10, 11P, 12, 17, or 20 – when shipped in bulk – may be hot (up to 250°F) at the time of shipment.

NFPA Hazard Class Health:1 Flammability:0 Reactivity:0

HMIS Hazard Class Health:1 Flammability:0 Reactivity:0

Appearance : Angular gray, white, and tan solid particles ranging in size from powder to boulders.

|                           |   |  |
|---------------------------|---|--|
| Odor                      | : | No odor  |
| Vapor pressure            | : | Not applicable   |
| Odor threshold            | : | Not applicable   |
| Vapor density             | : | Not applicable   |
| pH                        | : | 9.4 in saturated water solution  |
| Relative density          | : | Specific gravity = 2.7 – 2.9   |
| Melting/Freezing point    | : | Not applicable   |
| Solubility                | : | Negligible in water  |
| Flash point               | : | None   |
| Evaporation rate          | : | None   |
| Flammability              | : | Non flammable  |
| Auto ignition temperature | : | Non flammable  |
| Decomposition temperature | : | When heated at 1100 – 1700°F, dolomitic limestone decomposes into dolomitic quicklime releasing carbon dioxide gas.  |
| Viscosity                 | : | Not applicable.  |
| Reactivity                | : | The product is stable and non-reactive under normal conditions of use, storage and transport.  |
| Stability                 | : | Reacts with acids evolving CO <sub>2</sub> . Stable if no acids or strong oxidizing agents are present.  |
| Hazardous polymerization  | : | Will not occur.  |
| Incompatibility           | : | Ignites on contact with fluorine and other strong oxidizing agents and is incompatible with acids, ammonium salts, and magnesium metal. May cause pitting of aluminum. |

**Cleanup Procedures:** Spilled materials, where dust is generated, may overexpose clean-up personnel to respirable dust. Use of respiratory protective equipment may be necessary. Do not dry sweep or use compressed air for clean-up. Dolomitic limestone may be wetted with water to control dusting. Prevent spilled materials from entering streams, drains, or sewers. Waste disposal method: pick up and reuse clean materials. Dispose of waste materials only in accordance with applicable federal, state, and local laws and regulations.

**Recommendations on the conditions for safe storage:** May cause pitting of aluminum. Ignites on contact with fluorine and other strong oxidizing agents and is incompatible with acids, ammonium salts, and magnesium metal.

Selected Occupational Exposure Limits (effective, June 1, 2015)

1 – Value equivalent to OSHA formulas (29 CFR 1910.1000) and MSHA Metal/Non-Metal (1973 TVLs at 30 CFR 56/57 .5001)

2 – Value also applies to MSHA Metal/Non-Metal (19073 TVLs at 30 CFR 56/57 .5001)

3 – OSHA enforces 0.250 mg/m<sup>3</sup> in construction and shipyards (CPL-03-00-007).

4 – Value also applies to OSHA construction (29 CFR 1926.55, Appendix A) and shipyards (CPL-03-00-007).

5 – MSHA limit = 10 mg/m<sup>3</sup>.

6 – Value also applies to shipyards (29 CFR 1915), marine terminals (29 CFR 1917), and longshoring (29 Cfr 1918).

**US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)**

| Components   | Type | Value               | Form                  |
|--|------|---------------------|-----------------------|
| Particulates not otherwise classified (CAS SEQ250) | PEL  | 5 mg/m <sup>3</sup> | Respirable Fraction   |
|  |      | 15mg/m <sup>3</sup> | Total Dust            |
| Calcium Carbonate (CAS 1317-65-3)                  | TWA  | 5mg/m <sup>3</sup>  | Respirable Fraction 6 |
|  |      | 15mg/m <sup>3</sup> | Total Dust 5,6        |

**US. OSHA Table Z-3 (29 CFR 1910.1000)**

| Components   | Type | Value                  | Form                   |
|--|------|------------------------|------------------------|
| Crystalline Silica (Quartz) (CAS 14808-60-7)                                 | TWA  | 0.3 mg/m <sup>3</sup>  | Total Dust. 1,2,3      |
|  |      | 0.1 mg/m <sup>3</sup>  | Respirable. 1,2,3      |
|  |      | 2.4 mppcf              | Respirable. 1,2,3      |
| Particulates not otherwise classified (CAS SEQ250)                           | TWA  | 5 mg/m <sup>3</sup>    | Respirable fraction. 1 |
|  |      | 15mg/m <sup>3</sup>    | Total Dust. 1,4,5      |
|  |      | 50 mppcf               | Total Dust. 1,4        |
|  |      | 15 mppcf               | Respirable fraction. 1 |
| Tridymite and Cristobalite (other forms of crystalline silica) (CAS Mixture) | TWA  | 0.15 mg/m <sup>3</sup> | Total Dust. 1          |
|  |      | 0.05mg/m <sup>3</sup>  | Respirable. 1          |
|  |      | 1.2 mppcf              | Respirable. 1          |

**US. Acgih Threshold Limit Values**

| Components   | Type | Value                   | Form                |
|--|------|-------------------------|---------------------|
| Crystalline Silica (CAS 14808-60-7)  | TWA  | 0.025 mg/m <sup>3</sup> | Respirable Fraction |
| Tridymite and Cristobalite (other forms of crystalline silica) (CAS Mixture) | TWA  | 0.025 mg/m <sup>3</sup> | Respirable Fraction |

**US. NIOSH: Pocket Guide to Chemical Hazards**

| Components                          | Type | Value                                       | Form                                |
|-------------------------------------|------|---|-------------------------------------|
| Crystalline Silica (CAS 14808-60-7) | TWA  | 0.05 mg/m <sup>3</sup>                      | Respirable dust                     |
| Calcium Carbonate (CAS 1317-65-3)   | TWA  | 5 mg/m <sup>3</sup><br>10 mg/m <sup>3</sup> | Respirable fraction.<br>Total dust. |

**Exposure Guidelines:** OSHA PELs, MSHA PELs, and ACGIH TLVs and 8-hr TWA values. NIOSH RELs are for TWA exposures up to 10 hr/day and 40-hr/wk. Occupational exposure to nuisance dust (total and respirable) and respirable crystalline silica should be monitored and controlled. Terms including “Particulates Not Otherwise Classified”, “Particulates Not Otherwise Regulated”, “Particulates Not Otherwise Specified”, and “Inert or Nuisance Dust” are often used interchangeably; however, the user should review each agency's terminology for differences in meanings.

**Toxicological Information**

**Inhalation:** Repeated inhalation of respirable crystalline silica (quartz) may cause silicosis, a fibrosis (scarring) of the lungs. Silicosis is irreversible and may be fatal. Silicosis increases the risk of contracting pulmonary tuberculosis. Some studies suggest that repeated inhalation or respirable crystalline silica may cause other adverse health effects including lung and kidney cancer.

**Skin contact:** Limestone dust: May cause irritation through mechanical abrasion.

**Eye contact:** Limestone dust: May cause irritation through mechanical abrasion.

**Ingestion:** Not likely, due to the form of the product. However, accidental ingestion of the content may cause discomfort.

**Symptoms related to the physical, chemical, and toxicological characteristics:** Limestone dust:

Discomfort in the chest. Shortness of breath. Coughing.

**Information on toxicological effects:**

|  |   |   |
|--|---|---|
| Acute toxicity                         | : | Not expected to be acutely toxic.   |
| Skin corrosion/irritation              | : | This product is not expected to be a skin hazard.   |
| Serious eye damage and eye irritation: |   | Direct contact with eyes may cause temporary irritation.  |
| Respiratory or skin sensitization      | : | No respiratory sensitizing effects known.   |
| Skin Sensitization                     | : | Not known to be dermal irritant or sensitizer.  |
| Germ cell mutagenicity                 | : | than 0.1% are mutagenic or genotoxic.   |
| Carcinogenicity                        | : | Respirable crystalline silica has been classified by IARC and NTP as a known human carcinogen, and classified by ACGIH as a suspected human carcinogen.   |
| Aspiration hazard                      | : | Due to the physical form of the product it is not an aspiration hazard.   |
| Chronic effects                        | : | Prolonged inhalation of respirable crystalline silica may be harmful. May cause damage to organs (lungs) through prolonged or repeated exposure. There are reports in the literature suggesting that excessive crystalline silica exposure may be associated with autoimmune disorders and other adverse health effects involving the kidney. In particular, the incidence of scleroderma (thickening of the skin caused by swelling and thickening of fibrous tissue) appears to be higher in silicotic individuals. To date, the evidence does not conclusively determine a causal relationship between silica exposure and these adverse health effects. |

**Ecotoxicity:** Not expected to be harmful to aquatic organisms. Discharging limestone dust and fines into waters may increase total suspended particulate (TSP) levels that can be harmful to certain aquatic organisms.

**Other adverse effects:** No other adverse environmental effects (e.g., ozone depletion, photochemical ozone creation potential, global warming potential) are expected from this component.

US Federal Regulations: This product is a “Hazard Chemical” as defined by the OSHA Hazard

Communication Standard, 29 CFR 1910.1200

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D) – Not Regulated

U.S. TSCA Inventory List. All Chemical ingredients are listed.

RCRA Hazardous Waste Number: Not listed (40 CFR 261.33)

RCRA Hazardous Waste Classification (40 CFR 261): Not Classified

CERCLA Hazardous Substance List (40 CFR 302.4) Not Listed

CERCLA Reportable Quantity (RQ): not listed

SARA Hazard categories

Immediate hazard – no

Delayed hazard – yes

Fire hazard – no

Pressure hazard – no

Reactivity hazard – no

SARA311/312 Hazardous Chemical : yes SARA 313 (TRI Reporting) – Not Regulated

SARA Toxic Chemical (40 CFR 372.65): not listed

SARA 302 (Extremely Hazardous Substance): not listed

OSHA – Air contaminant (29 CFR 1910.1000, Table Z-1, Z-1-A)

Specifically Regulated Substance (29 CFR 1910): not listed

MSHA – not listed

Clean Air Act (CAA) Section 112 – Hazardous Air Pollutants (HAP's) List – Not Regulated

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130) – Not Regulated

Safe Drinking Water Act (SDWA) – Not Regulated

## **VI. Other Hazard Information**

### **Environmental Protection:**

**Appropriate engineering controls:** Use ventilation and dust collection to control exposure to below applicable limits.

**Recommendations for personal protective measures:** Respirable dust and quartz levels should be monitored regularly to determine worker exposure levels. Exposure levels in excess of allowable exposure limits should be reduced by all feasible engineering controls including (but not limited to) wet suppression, ventilation, process enclosure, and enclosed employee workstations.

Any special requirements for PPE:

Eye protection: Safety glasses with side shields should be worn as minimum protection. Dust goggles should be worn when excessively (visibly) dusty conditions are present or anticipated.

Skin protection: Use gloves to provide hand protection from abrasion. In dusty conditions wear long sleeve shirt. Wash work clothes after each use.

Respiratory Protection: All respirators must be NIOSH-approved for the exposure levels present. (See NIOSH Respirator Selection Guide). The need for respiratory protection should be evaluated by a qualified safety and health professional. Activities that generate dust require the use of an appropriate dust respirator where dust levels exceed or are likely to exceed allowable exposure limits. For respirable silica levels that exceed or are likely to exceed an 8 hr Time Weighted Average (TWA) of 0.5 mg/m<sup>3</sup>, a high efficiency particulate filter respirator must be worn at a minimum; however, if respirable silica levels exceed or are likely to exceed an 8 hr TWA of 5.0 mg/m<sup>3</sup> a positive pressure, full face respirator or equivalent is required. Respirator use must comply with applicable MSHA (42 CFR 84) or OSHA (29 CFR 1910.134) standards, which include provisions for a user training program, respirator inspection, repair and cleaning, respirator fit testing, medical surveillance and other requirements.

**Disposal Information:**

Disposal instructions: Do not allow this material to drain into sewers/water supplies. Dispose in accordance with all applicable regulations.

Hazardous waste code: Not regulated

Waste from residues: Disposal recommendations are based on the material as supplied. Disposal must be in accordance with current applicable laws and regulations, and material characteristics at time of disposal.

Contaminated packaging: Since emptied containers may retain product residue, follow label warnings even after container is emptied.

**Transport Information:**

DOT – not regulated as dangerous goods.

IATA – not regulated as dangerous goods.

IMDG – not regulated as dangerous goods.

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code** – not applicable. However, the product is covered under Appendix I of the IMSBC Code.

**Regulatory Information:**

US federal regulations: This product is not known to be a “Hazardous Chemical” as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200. All components are listed on or exempt from the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D) – not regulated

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) – not listed

CERCLA Hazardous Substance List (40 CFR 302.4) – not listed

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Immediate hazard – no

Delayed hazard – no

Fire hazard – no

Pressure hazard – no

Reactivity hazard – no

SARA 302 Extremely hazardous substance – not listed

SARA 311/312 Hazardous chemical – no

SARA 313 (TRI reporting) – not regulated

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List – not regulated

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130) – not regulated

Safe Drinking Water Act – not regulated

Food and Drug – total food additive

Administration (FDA) – direct food additive; GRAS food additive

### **Other Information:**

Further information: HMIS is registered trade and service mark of the NPCA. A HMIS Health rating including an \* indicates a chronic hazard.

HMIS ratings: Health: 1

Flammability: 0

Physical Hazard: 0

Abbreviations: LC50: Lethal Concentration, 50%; LD50: Lethal Dose, 50%

## **VII. Conditions of Sale and Warranty**

The directions of use for this product reflect the opinion of experts based on field use and tests. The directions are believed to be reliable and should be followed carefully. However, it is impossible to eliminate all risks inherently associated with use of this product. Crop injury, ineffectiveness, or other unintended consequences may result because of such factors as weather conditions, presence of other materials, or the manner of use or application all of which are beyond the control of Groenink's Elevator and Hardware, Inc. or the Seller. All such risks shall be assumed by the Buyer. Groenink's Elevator and Hardware, Inc. warrants that this product conforms to the chemical description on the label and is reasonably fit for the purposes referred to in its Direction for Use subject to the inherent risks referred to above. **Groenink's Elevator and Hardware, Inc USA makes no other express or implied Warranty of Fitness or Merchantability or any other express or implied warranty. In no case shall Groenink's Elevator and Hardware, Inc. or the Seller be liable for consequential, special, or indirect damages resulting from the use or handling of this Product.** Groenink's Elevator and Hardware, Inc. and the Seller offer this product, and the Buyer and user except it, subject to the foregoing Conditions of Sale and Warranty, which may be varied only by agreement in writing